

产品技术参数 PRODUCT TECHNICAL PAPAMETERS

60~100mA系列高压二极管 SERIES HV DIODES

型号 Type	反向重复 峰值电压 Repetitive Peak Reverse Voltage V_{RRM} (KV)	正向平 均电流 Avg. Forward Current $I_{F(AV)}$ (mA)	最大浪 涌电流 Maximum surge current I_{FSM} (A)	正向峰 值电压 Peak Forward Voltage V_{FM} (V)	反向峰 值电流 Peak reverse current I_{RRM1} I_{RRM2} (μA)		反向恢 复时间 Reverse Recovery Time T_{rr} (ns)	图号 Drawing No.
2CL2F	8	100	20	10	2	10	-	4
2CL2G	10	100	20	12	2	10	-	4
2CL2H	12	100	20	13	2	10	-	4
2CL2J	15	100	20	16	2	10	-	4
2CL2FF	8	60	10	16	2	15	150	4
2CL2FG	10	60	10	18	2	15	150	4
2CL2FH	12	60	10	20	2	15	150	4
2CL2FJ	15	60	10	24	2	15	150	4
2CL2FK	10	100	10	22	2	15	100	4
2CL2FL	15	100	10	26	2	15	100	4
2CL2FM	20	100	10	35	2	15	100	4
2CL2FP	30	100	10	45	2	15	100	4
2CL2FR	35	100	10	50	2	15	100	4

